

eXLink receptacle 7-pole/6-pole + PE



Plastic

Metal

Ordering key eXLink receptacle 6+1-pole/7-pole
Metal version for Ex-d application for volume >2000 cm³

GHG 572 8XXX RXX0X

X = Count No.

see page 2.1.140 point 7.

1. Connection technology	2. Coding	3. Material	4. Accessories
1 = Crimp ¹⁾ /30 cm multi wire up to 1.5 mm ²	04 = 4 h	0 = Plastic	0 = without padlocking facility
2 = Crimp ¹⁾ /30 cm multi wire up to 2.5 mm ²	06 = 6 h	1 = Stainless steel AISI 316L with M25 thread	9 = with padlocking facility
¹⁾ Crimp only in plastic version	08 = 8 h	3 = Nickel-plated brass with M25 thread	
	10 = 10 h	5 = Stainless steel AISI 316L with 3/4" NPT thread	
	12 = 12 h	6 = Nickel-plated brass with 3/4" NPT thread	

Metal version only potted with multi-wire.
All versions including protection cap.

Ordering details

Voltage	No. of poles	Coding	Power connection	Thread	
				M25 x 1.5 Order No.	3/4" NPT Order No.
Flange socket made of plastic					
110 V AC	6-pol + PE	4 h	Crimp up to 1.5 mm ²	GHG 572 8104 R0001	
110 V AC	6-pol + PE	4 h	Crimp up to 2.5 mm ²	GHG 572 8204 R0001	
230 V AC	6-pol + PE	6 h	Crimp up to 1.5 mm ²	GHG 572 8106 R0001	
230 V AC	6-pol + PE	6 h	Crimp up to 2.5 mm ²	GHG 572 8206 R0001	
24 V DC	7-pol	8 h	Crimp up to 1.5 mm ²	GHG 572 8108 R0001	Only available in metal version!
24 V DC	7-pol	8 h	Crimp up to 2.5 mm ²	GHG 572 8208 R0001	
400 V AC	6-pol + PE	10 h	Crimp up to 1.5 mm ²	GHG 572 8110 R0001	
400 V AC	6-pol + PE	10 h	Crimp up to 2.5 mm ²	GHG 572 8210 R0001	
24 V AC	6-pol + PE	12 h	Crimp up to 1.5 mm ²	GHG 572 8112 R0001	
24 V AC	6-pol + PE	12 h	Crimp up to 2.5 mm ²	GHG 572 8212 R0001	
110 V AC	6-pol + PE	4 h	30 cm multi wire 1.5 mm ²	GHG 572 8104 R0002	Only available in metal version!
110 V AC	6-pol + PE	4 h	30 cm multi wire 2.5 mm ²	GHG 572 8204 R0002	
230 V AC	6-pol + PE	6 h	30 cm multi wire 1.5 mm ²	GHG 572 8106 R0002	
230 V AC	6-pol + PE	6 h	30 cm multi wire 2.5 mm ²	GHG 572 8206 R0002	
24 V DC	7-pol	8 h	30 cm multi wire 1.5 mm ²	GHG 572 8108 R0002	
24 V DC	7-pol	8 h	30 cm multi wire 2.5 mm ²	GHG 572 8208 R0002	
Flange socket made of nickel-plated brass					
110 V AC	6-pol + PE	4 h	30 cm multi wire 1.5 mm ²	GHG 572 8104 R3001	GHG 572 8104 R6001
110 V AC	6-pol + PE	4 h	30 cm multi wire 2.5 mm ²	GHG 572 8204 R3001	GHG 572 8204 R6001
230 V AC	6-pol + PE	6 h	30 cm multi wire 1.5 mm ²	GHG 572 8106 R3001	GHG 572 8106 R6001
230 V AC	6-pol + PE	6 h	30 cm multi wire 2.5 mm ²	GHG 572 8206 R3001	GHG 572 8206 R6001
Flange socket made of stainless steel					
110 V AC	6-pol + PE	4 h	30 cm multi wire 1.5 mm ²	GHG 572 8104 R1001	GHG 572 8104 R5001
110 V AC	6-pol + PE	4 h	30 cm multi wire 2.5 mm ²	GHG 572 8204 R1001	GHG 572 8204 R5001
230 V AC	6-pol + PE	6 h	30 cm multi wire 1.5 mm ²	GHG 572 8106 R1001	GHG 572 8106 R5001
230 V AC	6-pol + PE	6 h	30 cm multi wire 2.5 mm ²	GHG 572 8206 R1001	GHG 572 8206 R5001